FX2NC-32BL Battery MODEL CODE : 09M129

### STARTUP AND MAINTENANCE PRECAUTIONS E

## 

- PRECAUTIONS
  Use the battery for memory backup correctly in conformance to the manual of each product.
  Use the battery only for the specified purpose.
  Connect the battery correctly.
  Do not charge, disassemble, heat, put in fire, short-circuit, connect reversely, weld, swallow or burn up the battery. or apply excessive forces (Vibration, impact, drop, etc.) on the battery.
  Do not store or use the battery in a place at high temperature or exposed to direct sunlight.
  Do not stores to water, bring near fire or touch the contents such as liqui leakage directly.
  Incorrect handling of the battery may cause heat excessive generation, burst, ignition, liquid leakage of communication, and lead to injury, fire or failures and malfunctions; of facilities and other equipment. burst, ignition, liquid leakage or deformation, and lead to injury, fire of failures and malfunctions of facilities and other equipment. Power of the Devices with Built-in Batterest (all phase) before attaching/detaching the battery. Failure to do so may cause electric shock or damage to the product.
- Please contact a certified electronic waste disposal company for the environmentally safe recycling and disposal of your device.

#### 1. Applicable model

Product name	Applicable model					
FX2NC-32BL	FX2NC, FX2N-20GM, F930GOT, F940GOT-H/-RH					

#### 2. Battery Replacement

For the replacement procedure, refer to the User's Manual of the respective Devices with Built-in Batteries.



原产地 日本国 合格证 首和 Made in Japan MITSUBISHI ELECTRIC CORPORATION

#### 3. Battery Life

- Battery life: Approx. 3 years (ambient temperature: 25°C) Replacement period: Within 2 or 3 years (Due to natural discharge within all batteries, please prepare a replacement before the above-stated replacement period.) For details, refer to the User's Manual of the respective Devices with Built-in Batteries.

#### $\nabla$

# 4. Precautions for Battery Transportation When transporting lithium batteries, follow the transportation regulations

regulations.	

Product name	Battery type	Product supply status	Lithium Content (gram/unit)	Mass <sup>*1</sup> (gram/unit)				
FX2NC-32BL	lithium metal battery	Cell	0.15	30				
to The velve indicates the mass with performing								

ates the mass with p

Comply with IATA Dangerous Goods Regulations, IMDG code and the local transport regulations when transporting products listed ho Also, consult with the shipping carrier.



含有有害6物质的名称,含有量,含有部品 本产品中所含有的有害6物质的名称,含 含有量, 含有部品如 下表所示。

部件名称		有害物质					
		铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多溴 二苯醚 (PBDE)
可编程 控制器	外壳	0	0	0	0	0	0
	印刷基板	×	0	0	0	0	0

产品中有害物质的名称及含量

本表格依据SJ/T 11364的规定编制。

○:表示该有害物质在该部件所有均质材料中的含量均在GB/T

26572规定的限量要求以下。 ※:表示该有害物质至少在该部件的某一均质材料中的含量超出 GB/T 26572规定的限量要求。

基于中国标准法的参考规格: GB/T15969.2