

FX3U-FLROM-16/64/64L/1M Hardware Manual

The FX3U-FLROM-16/64/64L/1M memory cassette is a flash memory unit used as program memory for the FX3U/FX3UC PLC.

1. Specifications

Applicable. Check for the version in parentheses.

Model name		FX3U- FLROM-16	FX3U- FLROM-64	FX3U- FLROM-64L	FX3U- FLROM-1M			
Applicable PLC	FX3U PLC	✓	✓	✓	√(Ver.3.00 or later)			
	FX3UC PLC	√(Ver.2.20 or later)	✓	√(Ver.2.20 or later)	√(Ver.3.00 or later)			
Max. memory capacity		16000 steps	64000 steps	64000 steps	*1			
Memory type		Flash memory						
Max. Allowable Write		10000 times						
PROTECT switch		Provided						
Data transfer button		NA	NA	Provided	NA			
*1 64000 steps (program capacity) + 1300KB (symbolic information capacity)								

2. Handling Cautions

- 2. Handling Cautions
 For further installation and PROTECT switch details, refer to the User's Manual Hardware Edition of the respective PLC.
 Power off the PLC before attaching/detaching the memory cassette.
 The PLC ERROR (ERR) LED may flicker to indicate a program error when using the product for the first time.
 I such a case, perform an "All Clear" or "Program transfer" by a programming tool.
 Connect the memory cassette securely to the prescribed connector. A poor connection can cause malfunctions.
 Installing the cassette in a raised or tilted posture can also cause malfunctions.

Cross-section drawing (memory cassette installation condition)

The stage in which the whole memory cassette fell.

PLC body *1: Mem > PLC body *1: Memory

*1 Raised cassett



997D12801G

Bad





地 日本国 合格证

Made in Japan MITSUBISHI ELECTRIC CORPORATION

Bad *1 Tilted casse

3. Applicable standard

STAUFIROM-16/64/64L/1M complies with EC directive (EMC Directive).
Further information can be found in the following manual.
However, FXuJ-FLROM-64 made in June, 2005 or later complies with EC directive (EMC Directive). FX3UC-32MT-LT does not comply with EC directive (EMC Directive).

— FX3U Series Hardware Manual (Manual No. JY997D50301)

). s Hardware Manual (Manual No. JY997D50301) → FX3UC (D, DS, DSS) Series Hardware Manual (Manual No. JY997D50501) → FX3UC-32MT-LT-2 Hardware Manual

(Manual No. JY997D31601)

含有部品如

Attention This product is designed for use in industrial applications.

lanufactured by eu by. Mitsubishi Electric Corporation 2-7-3 Marunouchi, Chiyoda-ku, Tokyo, 100-8310 Japan

 ∇



「电器电子产品有害物质限制使用标识要求」的表示方式 Note: This symbol mark is for China only.



部件夕称

含有有害6物质的名称,含有量,含有部品 含有量,

本产品中所含有的有害6物质的名称, 下表所示。

产品中有害物质的名称及含量

有害物质

HELL HAW		铅 (Pb)	汞 (Hg)	镉 (Cd)	六价铬 (Cr(VI))	多溴联苯 (PBB)	多决 二苯醚 (PBDE)
可编程 控制器	外壳	0	0	0	0	0	0
	印刷基板	×	0	0	0	0	0
本表格依	t据SJ/T 1	1364É	的规定	三编制			

- 〇:表示该有害物质在该部件所有均质材料中的含量均在GB/ 26572规定的限量要求以下。 <:表示该有害物质至少在该部件的某一均质材料中的含量超出
- GB/T 26572规定的限量要求。